

JM802H FULL HYDRAULIC DOUBLE DRUM VIBRATORY ROLLER



Application:

Compacting and repairing the general road base and asphalt pavement in narrow space, such as sidewalks, rural county road, parking area, stadium, trench, courtyard and so on. The highway road base and asphalt pavement are also suitable.

Main features:

1. Hydraulic double drum drive, two-speed range and stepless speed change;
2. Hydraulic double drum vibration, electronic controlled delayed starting of vibration with good compaction performance;
3. Hydraulic steering, articulated frame with flexible operation;
4. Equipped with electronic control pressurized water spraying system, high volume anti-corrosive water tank;
5. Hydraulic service brake, electronic control disc brake parking brake, safe and reliable;
6. The front engine cover can be turned up in a big angle for easy maintenance;
7. Equipped with imported famous brand hydraulic components with reliable performance;
8. A trailer is provided for convenient transportation;
9. Imported Perkins engine is optional for you.

Technical parameters

Item	Unit	JM802H
Operating Weight	kg	2000
Rolling width	mm	1000
Vibration frequency	Hz	65
Theoretical amplitude of vibration	mm	0.45
Exciting force	kN	21
Travel speed	Km/h	0~4/0~8
Engine model		3M78
Engine power/speed	Kw/r/min	18.4/2600
Overall dimensions(L*W*H)	mm	2330×1140×2530